

Features


- Ⓢ RoHS compliant
- Ⓢ Magnetic shield construction
- Ⓢ CompositeMagnetic powder core
- Ⓢ Handle transient current spikes without saturation
- Ⓢ Ultra low buzz noise due to composite construction
- Ⓢ Rated voltage: 30V Max.
- Ⓢ Moisture Sensitivity Level (MSL): 1
- Ⓢ Excellent temperature stability for inductance and saturation
- Ⓢ Operating temperature rang(Including temperature rise):
-55°C to +125°C

Applications

- Ⓢ DC/DC converters
- Ⓢ Battery powered devices
- Ⓢ Low profile ,high current power supplies
- Ⓢ PDA/notebook/desktop/server applications



Mechanical Dimensions (Units:mm)




Electrical Specifications

Part Number	L (μ H)	DCR (m Ω)		I _{rms} (A)	I _{sat} (A)
		Typ.	Max.		
MHA0415NSGR10M	0.10 ± 20%	4.40	5.30	6.80	19.0
MHA0415NSGR22M	0.22 ± 20%	7.90	9.50	5.20	12.0
MHA0415NSGR33M	0.33 ± 20%	9.50	11.4	4.50	9.00
MHA0415NSGR47M	0.47 ± 20%	12.0	14.4	4.00	8.00
MHA0415NSGR56M	0.56 ± 20%	18.5	22.0	3.40	7.00
MHA0415NSGR68M	0.68 ± 20%	21.5	25.5	3.00	6.00
MHA0415NSG1R0M	1.00 ± 20%	33.5	40.0	2.40	5.50
MHA0415NSG1R5M	1.50 ± 20%	52.0	62.5	2.00	4.50
MHA0415NSG2R2M	2.20 ± 20%	78.5	94.0	1.60	3.50

Notes:

1. All of the electrical specifications are test at 25°C, inductance test at 100KHz/0.25V.
 2. I_{rms} is the current that caused a approximate 40°C temperature rise from 25°C ambient.
 3. I_{sat} is the DC current at which inductance drop approximately 30% from its value without current.
 4. The part temperature(ambient + temp.rise) should not exceed 125°C under worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
 5. Due to product improvement, Product specifications May be changed discontinuously without advance notice.
- Please contact with sales representatives or product engineers, and the Mentech product approval sheet shall be obtained before ordering.

Packaging Specifications (Units:mm)



3000Pcs/Reel	12 Reels/Carton
	36000Pcs/Carton