



FEATURES

- RoHS compliant,UL94V-0
- Small size (7.3*6.8mm Max),low profile(Height:5.0mm Max)
- Inductance range from 0.13uH to 47.0uH
- Surface mount design
- Magnetic shield construction
- Ultra low buzz noise due to composite construction
- Handle transient current spikes without saturation
- Excellent temperature stability for inductance and saturation
- Tape & reel packing
- Solder profile acc.J-STD-020D

APPLICATIONS

- Low profile ,high current power supplies
- DC/DC converters
- Battery powered devices
- PDA/notebook/desktop/server applications



Part number	Inductance (μ H \pm 20%)	DCR (m Ω) @25 $^{\circ}$ C		I _{rms} (A)	I _{sat} (A)
		TYP.	MAX.		
MHA0750NSGR13M	0.13	1.00	1.20	42.00	48.00
MHA0750NSGR22M	0.22	1.10	1.30	30.00	35.00
MHA0750NSGR36M	0.36	2.70	3.10	21.00	25.00
MHA0750NSGR40M	0.40	3.20	3.50	20.00	23.00
MHA0750NSGR47M	0.47	3.25	3.75	20.00	21.00
MHA0750NSGR56M	0.56	3.40	3.60	18.00	20.00
MHA0750NSGR68M	0.68	3.90	4.20	16.50	18.00
MHA0750NSGR82M	0.82	4.60	4.90	16.00	17.00
MHA0750NSG1R0M	1.00	5.60	6.50	12.50	15.00
MHA0750NSG1R2M	1.20	6.70	7.50	11.00	13.00
MHA0750NSG1R5M	1.50	6.70	7.50	11.00	12.00
MHA0750NSG2R2M	2.20	11.20	12.50	9.00	10.00
MHA0750NSG3R3M	3.30	19.90	20.90	8.50	9.00
MHA0750NSG4R7M	4.70	26.00	29.00	6.00	8.00
MHA0750NSG5R6M	5.60	31.50	34.40	6.00	7.00
MHA0750NSG6R8M	6.80	36.50	41.00	5.50	6.00
MHA0750NSG8R2M	8.20	40.00	43.00	5.50	5.50
MHA0750NSG100M	10.0	54.00	60.00	4.50	5.30
MHA0750NSG120M	12.0	58.00	65.00	4.00	5.00
MHA0750NSG150M	15.0	78.00	90.00	3.10	4.00
MHA0750NSG180M	18.0	83.00	105.0	3.00	3.50
MHA0750NSG220M	22.0	120.0	140.0	2.60	3.50
MHA0750NSG330M	33.0	165.0	190.0	2.30	3.00
MHA0750NSG470M	47.0	250.0	290.0	2.00	2.50

ABSOLUTE MAXIMUM RATINGS

Operating temperature rang (Including coil' self temperature rise)	-55 $^{\circ}$ C to +125 $^{\circ}$ C
Storage temperature rang	-55 $^{\circ}$ C to +125 $^{\circ}$ C

SOLDERING INFORMATION

Peak reflow temperature	250 $^{\circ}$ C
Pin finish	tin

PACKAGING INFORMATION

Tape&Reel	1000pcs per reel
Weight	1.2g/pcs

Notes

1. Electrical specification at 25 $^{\circ}$ C.
2. Inductance tested at 100 kHz, 0.25Vrms.
3. I_{rms} is the current that caused a approximate 40 $^{\circ}$ C temperature rise from 25 $^{\circ}$ C ambient.
4. I_{sat} is the DC current at which inductance drop approximately 30% from its value without current.
5. The part temperature(ambient + temp.rise) should not exceed 125 $^{\circ}$ C under worst case operating conditions.Circuit design,component placement, PWB trace size and thickness,airflow and other cooling provisions all affect the part temperature.Part temperature should be verified in the end application.